



PROJECT
TYPE
CATALOG #

## 5" Recessed Downlighting



### 06-5C-NIC

FOR NEW WORK APPLICATIONS

- Housing adjusts to accommodate up to 1.5" thick ceilings
- 7 1/2" height allows use in 2" x 8" joist construction.
- Integral T-Bar installation slots



### 06-5C-RIC

FOR REMODEL APPLICATIONS

- Housing adjusts to accommodate up to 2" thick ceilings
- Units slips through 5 3/8" ceiling opening
- Four remodel clips secure housing



## FEATURES

### 06-5C-NIC / 06-5C-RIC

- For direct contact with insulation
- Thermally-protected
- Adjustable socket bracket to adjust proper lamp position or socket snaps into trim for consistent lamp positioning
- Wire-through junction box
- Housing adjusts to accommodate up to 2" thick ceilings
- Four Romex pry-outs with strain relief
- Lamp: Max 75W R30/PAR30

## TRIMS



Fresnel Lens  
6.5" O.D.  
40W / A19  
50W or PAR20  
06-ST-FS



White Gimbal  
6.5" O.D.  
75W or PAR30  
06-ST-GR



Reflector Splay Trim  
6.5" O.D.  
75W R/PAR30  
06-ST-BW-REFLECTOR



White Cone Baffle-Air Tight  
6.5" O.D.  
75W R/PAR30  
06-ST-ATC



Clear Cone Reflector  
6.5" O.D.  
75W R/PAR30  
06-ST-RC-ATC

## OPTIONS

When ordering specify suffix:

"AT" for air-tight housing

"Q" for quick connector

"N" for nail hanger bars

"E" for electrical transformer