Δ" **MINI DOWNLIGHT RECESSED CANS & TRIMS**



- 06-4C-N
- FOR NEW WORK APPLICATIONS
- Adjustable hanger bar with 16" to 24" joist span
- 5" height allows use in 2" x 8" joist construction

• 3-inch clearance of insulation required.

• 3-inch clearance of insulation required.

• For direct contact with insulation.

• For direct contact with insulation.

STANDARD 06-4C DIMENSIONS

STANDARD 06-4C FEATURES

STANDARD 06-4C RIC DIMENSIONS

• Adjustable housing for various ceiling thickness • "Nailess" installation bar hangers (New Work)

• UL Listed for feed-through wiring and damp location.

Integral T-Bar installation slots (New Work)

• For new work applications where low-plenum or 6" joists are present

• For old work or remodel applications where low-plenum or 6" joists are

• For new work applications and where low-plenum or 6" joists are present

• For old work or remodel applications where low-plenum of 6" joists are

• Oversized pre-wired snap on J-Box with 4 integral Romex pry-outs with

• Integral T-Bar installation slots

FEATURES 06-4C-N

06-4C-R

06-4C-NIC

06-4C-RIC

4 ¼" W x 5 ½" H

4 ¼" W x 6 ¼" H

• Thermally-protected

• Adjustable lamp height

strain reliefs

present

present



• Integral T-Bar installation slots



PROJEC[®]

FOR REMODEL APPLICATIONS

- Four remodel clips to secure housing
- Units slips through 4 1/8-4 1/2" ceiling opening





06-4C-RIC

FOR REMODEL APPLICATIONS

- · Four remodel clips to secure housing
- Units slips through 4 1/8-4 1/2" ceiling opening
- · Direct contact with insullation









Black Stepped Baffle 5″ O D 50W/R20 or PAR20



Gimbal Ring - White 5″ O.D. 50W/R20 or PAR20

```
Albalite Shower - White
```

5" O.D. 5″ O.D. 50W/R20 or PAR20 50W/R20 or PAR20 Note: Many trims are available in a mocha or champagne finish, please consult factory.

White Stepped Baffle









When ordering specify suffix:

"AT" for air-tight housing



CONTRACTOR

NG & SUPPL

06-4C-NIC

FOR NEW WORK APPLICATIONS Housing adjusts to accommodate up to 1.5" thick ceilings • 5" height allows use in 2" x 8" joist construction.





5" O D

50W/R20 or PAR20



- "Q" for quick connector "N" for nail hanger bars

Contractor Lighting Supply • (877)-664-5483 • www.contractorlighting.com





5″ O D

