



PROJECT
TYPE
CATALOG #

6" RECESSED DOWNLIGHTING



FEATURES

06-6C-NICAT-N

- 6½"W x 7½"H
- For new work applications.
- For direct contact with insulation
- Up to 75-watt lamp with proper trim
- Thermally-protected
- "Nainless" installation slots
- Integral T-bar installation slots
- Oversized J-Box with 4 integral Romex pry-outs with strain reliefs
- UL Listed for both drywall and drop ceilings.
- Adjustable lamp height
- UL Listed for feedthrough wiring and damp location

06-6C-RICAT

- 6½"W x 7½"H
- For old work or remodel applications
- For direct contact with insulation
- Up to 75-watt lamp with proper trim
- UL Listed for both drywall and drop ceilings
- Thermally-protected
- Adjustable lamp height
- UL Listed for feed-through wiring and damp location

OPTIONS

When ordering specify suffix:

- "AT" for air-tight housing
- "E" for Electronic Transformer
- "IC" for Insulated Rated
- "N" for Nail Hanger Bars

TRIMS



Eyeball - white
8" O.D.
75W/R30 or PAR 30
(Specify: SN for satin nickel)



White Stepped Baffle
7" O.D.
75W/R30 or PAR 30
150W/R40 or PAR38
(Specify: SN for satin nickel)



Albalite Shower
8" O.D.
40W/A19
(Specify: SN for brushed
satin nickel)



Fresnel Lens
8" O.D.
60W / A19



Black Stepped Baffle
7" O.D. w/ regressed
eyeball
75W/R30 or PAR 30



Black Stepped Baffle
7" O.D.
75W/R30 or PAR 30
150W/R40 or PAR38
(Specify: SN for satin nickel)



Black Stepped Baffle
8" O.D. wide ring
75W/R30 or PAR 30



Open trim - white
8" O.D.
75W/R30 or PAR 30
(Specify: PB for polished brass)



Open trim - white
8" O.D.
75W/R30 or PAR 30



Air Tight Clear Reflector
7" O.D.
90W/R40 or PAR30



Dropped opal shower
8" O.D.
40W/A19