


| PROJECT |
|-----------|
| |
| |
| ТҮРЕ |
| |
| |
| CATALOG # |
| |
| |

LED EXIT SIGNS

Slim and Low profile LED exit Sign provides a crisp, clean look and excellent energy savings.







ELECTRICAL

- Dual 120/277 voltage.
- Charge rate/power "ON" LED indicator light and push to test switch for mandated code compliance testing.
- 4.8V Long-life, maintenance-free, rechargeable NiCd battery.
- Internal solid-state transfer switch automatically connects the internal battery to LED board for minimum 90-minute emergency illumination.

• Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.

WARRANTY / LISTING

• Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.

• UL listed for damp locations. (0°C - 50°C).

• Five year warranty of all electronics and housing. Battery pro-rated for five years.

ILLUMINATION

• Ultra bright, energy efficient, long life Red or Green LED.

ORDERING INFORMATION

HOUSING

• Injection-molded, engineering-grade, 5VA flame retardant, high-impact resistant, thermoplastic in white or black finish.

- EZ snap-out chevron directional indicators.
- Compact, low-profile design.

OPTIONS

• 2C: Dual circuit option on the AC-only unit enables it to be connected to two different (one acting as a back-up to the other) supplie at the same time.

• SDT: Self-diagnostic feature performs monthly, biannual, and annual tests to ensure reliable operation and meet electrical and life safety codes.

- Custom: Signs available with requested 'special' wording.
- USA: Substantial transformation assembly in the U.S. complies with "Assembled in the USA" under the Buy American Act.
- cUL: Units tested to meet requirements of CAN/CSA-c22.2 No. 141-02 standard for unit equipment.

MOUNTING

- EZ-snap mounting canopy included for top or end mount.
- Universal K/O pattern on back plate for wall mount.

| MODEL | No. of FACES | BATTERY | LETTER COLOR | HOUSING COLOR | | OPTIONS |
|-------|--|---------------------------------------|------------------|--------------------|-----------------------------------|--|
| 02-XP | 1 Single Face 2 Single/Double Face | Blank AC Only EM Battery Backup | R Red G Green | W White B Black | SDT 2C Custom USA cUL | Self-diagnostics ¹ Dual circuit operation ² Custom wording Assembled in USA cUL Listed |

Special voltage and SALIDA face plate options available. Check with your Contractor Lighting & Supply representative.

¹ Available only with EM units ² Available only with AC units.

010919 Contractor Lighting & Supply · (877)-664-5483 · www.contractorlighting.com