



PROJECT
TYPE
CATALOG #

## LED RECESSED CANS / TRIMS

### 06-6C-NICATLED-NND DESCRIPTION

6" LED dedicated IC housing, 06-6C-NICATLED-NND is designed for new construction installations and suitable for use in ceilings where the housing can be direct contact with insulation. Air tight construction reduces energy costs by reducing the amount of air leakages through the ceiling.

### FEATURES

- Galvanized steel construction. The housing can be removed from the plaster frame to provide access to the junction box.
- Listed for through branch circuit wiring.
- Contains one 1½", six ⅞" knockouts and four Romex pryouts with strain relief.
- Pre-installed real nail easily installs in regular lumber, engineered lumber.
- Bar Hangers are adjustable from 13½" to 25" and can be repositioned 90° on plaster frame.
- cULus Listed for Damp Location.
- cULus Listed for Feed Through.
- Certified under ASTM-E283 for Air tight construction
- Meets state of California title 24 requirements.

### 06-6C-RICATLED-RND DESCRIPTION

6" LED dedicated IC housing, 06-6C-RICATLED-RND is designed for remodel applications and suitable for use in ceilings where the housing can be direct contact with insulation. Air tight construction reduces energy costs by reducing the amount of air leakages through the ceiling.


### FEATURES

- Listed for through branch circuit wiring.
- Contains one 1½", six ⅞" knockouts and four Romex pryouts with strain relief.
- Housing adjusts from ⅝" to 1⅜" to accommodate various ceiling thickness.
- Four remodel clips secure housing and accommodates ½" and ⅝" ceiling materials.
- cULus Listed for Damp Location.
- cULus Listed for Feed Through.
- Certified under ASTM-E283 for Air tight construction
- Meets state of California title 24 requirements.


### 06-6C-NICATLED-NND



### DIMENSIONS




**6" IC LED  
Dedicated Can  
New Construction**



### 06-6C-RICATLED-RND



### DIMENSIONS



**6" IC LED  
Dedicated Can  
Remodel**

